US ERA ARCHIVE DOCUMENT



OMB No. 2060-0336, Approval Expires 04/30/2012

Federal Operating Permit Program (40 CFR Part 71)

CERTIFICATION OF TRUTH, ACCURACY, AND COMPLETENESS (CTAC)

This form must be completed, signed by the "Responsible Official" designated for the facility or emission unit, and sent with each submission of documents (i.e., application forms, updates to applications, reports, or any information required by a part 71 permit).

A. Responsible Official
Name: (Last) (First) (MI)
TitleTribal Chairman
Street or P.O. Box 2330 Sioux Trail NW
City Prior Lake State MN ZIP 55372
Telephone (_952) _4966109 Ext Facsimile ()
B. Certification of Truth, Accuracy and Completeness (to be signed by the responsible official)
I certify under penalty of law, based on information and belief formed after reasonable inquiry, the statements and information contained in these documents are true, accurate and complete.
Name (signed) ** () - j
Name (typed) Charlie Vig Date: 10 / 8 / 2014



United States Environmental Protection Agency Program Address Phone Fax Web address Genevieve Damico, Chief, Air Permits Section U.S. Environmental Protection Agency, Region 5 77 West Jackson Blvd (AR-18J) Chicago, IL 60604 phone: (312) 353-4761

fax: (312) 385-5501 email: damico.genevieve@epa.gov

-

FEDERAL MINOR NEW SOURCE REVIEW PROGRAM IN INDIAN COUNTRY

Application for New Construction

(Form NEW)

Please check all that apply to show how you are using this form:

Proposed Construction of a New Source Proposed Construction of New Equipment at an Existing Source X Proposed Modification of an Existing Source Other – Please Explain

Please submit information to:

Genevieve Damico, Chief, Air Permits Section U.S. Environmental Protection Agency, Region 5 77 West Jackson Blvd (AR-18J) Chicago, IL 60604

Phone: (312) 353-4761

A. GENERAL SOURCE INFORMATION

1. (a) Company Name		2. Source Name			
Shakopee Mdewakanton Sioux (b) Operator Name	(Community	Dakotah! Sport and Fitnes	ss .		
Shakopee Mdewakanton Sioux	Community				
3. Type of Operation Amuseme	nt and Recreation Services,	4. Portable Source?	Yes No X		
Fitness and Recreational Sports Ce	enters, Electricity	5. Temporary Source?	Yes No X		
6. NAICS Code 71394, 62131,	62134	7. SIC Code 7991, 8041, 8049			
8. Physical Address (home base MN, 55372	for portable sources) Dakot	ta Sport and Fitness 2100 Tr	ail of Dreams, Prior Lake,		
9. Reservation*Shakopee	10. County*	11a. Latitude*	11b. Longitude*		
Mdewakanton Sioux Community	See Below	See Below	See Below		
12a. Quarter Quarter Section* 12b. Section*		12c. Township*	12d. Range*		
See Below	See Below	See Below	See Below		

*Provide all proposed locations of operation for portable sources

EPA Form No. 5900-248

Generator and Stack Location Coordinates

Generator UTM Coordinates						rdinates	Township and Range
/Stack	Latitude	Longitude	Latitude	Longitude	E	N	Quarter/Quarter
EU 204	44.724992	-93.47819	44°43.49953'	-093°28.69138'	15T 462131.48mE	4952512.46mN	MN Fifth T115N R22W S33

B. PREVIOUS PERMIT	ACTIONS (Provide information in this format for each permit that	has
been issued to this source.	Provide as an attachment if additional space is necessary)	

Source Name on the Permit Shakopee Mdewakanton S	
Permit Number MIN-SM-27139R004-2013-01	and the second s
	What is a second of the second
Date of the Permit Action 23 Jun 2014	
Date of the Fermit Action 25 Jun 2014	
Source Name on the Permit	
Permit Number (xx-xxx-xxxx-xxxxxxx)	
Date of the Permit Action	
Source Name on the Permit	
Permit Number (xx-xxx-xxxx-xxxx.xx)	
Date of the Permit Action	
Source Name on the Permit	
Permit Number (xx-xxx-xxxx-xxxx)	
Date of the Permit Action	
Source Name on the Permit	
Permit Number (xx-xxx-xxxx-xxxxxxxxxxxxxxxxxxxxxxxxx	
Date of the Permit Action	

C. CONTACT INFORMATION

Company Contact Stanley Ellison		Title Director of Land and Natural Resources	
Mailing Address Shakopee Mdewakanton Sioux	Community , 2330 Sioux	Trail	NW, Prior Lake, MN, 55372
Email Address stan.ellison@shakopeedakota.org			
Telephone Number (952)496-6158			imile Number) 445-8906
Operator Contact (if different from company contact) SAME AS COMPANY CONTACT		Title	
Mailing Address			
Email Address			
Telephone Number	Facsimile Number		
Source Contact SAME AS COMPANY CONTACT		Title	,
Mailing Address			
Email Address			
Telephone Number	Facsimile Number		
Compliance Contact SAME AS COMPANY CONTACT	Title	·	
Mailing Address			
Email Address			
Telephone Number	Facsimile Number		

D. ATTACHMENTS

Include all of the following information (see the attached instructions)

FORM SYNMIN - New Source Review Synthetic Minor Limit Request Form, if synthetic minor limits are being requested.

Narrative description of the proposed production processes. This description should follow the flow of the process flow diagram to be submitted with this application.

Process flow chart identifying all proposed processing, combustion, handling, storage, and emission control equipment.

A list and descriptions of all proposed emission units and air pollution-generating activities.

Type and quantity of fuels, including sulfur content of fuels, proposed to be used on a daily, annual and maximum hourly basis.

Type and quantity of raw materials used or final product produced proposed to be used on a daily, annual and maximum hourly basis.

Proposed operating schedule, including number of hours per day, number of days per week and number of weeks per year.

A list and description of all proposed emission controls, control efficiencies, emission limits, and monitoring for each emission unit and air pollution generating activity.

Criteria Pollutant Emissions - Estimates of Current Actual Emissions, Current Allowable Emissions, Post-Change Uncontrolled Emissions, and Post-Change Allowable Emissions for the following air pollutants: particulate matter, PM₁₀, PM_{2.5}, sulfur oxides (SOx), nitrogen oxides (NOx), carbon monoxide (CO), volatile organic compound (VOC), lead (Pb) and lead compounds, fluorides (gaseous and particulate), sulfuric acid mist (H₂SO₄), hydrogen sulfide (H₂S), total reduced sulfur (TRS) and reduced sulfur compounds, including all calculations for the estimates.

These estimates are to be made for each emission unit, emission generating activity, and the project/source in total.

Modeling - Air Quality Impact Analysis (AQIA)

ESA (Endangered Species Act)

NHPA (National Historic Preservation Act)

E. TABLE OF ESTIMATED EMISSIONS

The following tables provide the total emissions in tons/year for all pollutants from the calculations required in Section D of this form, as appropriate for the use specified at the top of the form.

E(i) – Proposed New Source

Pollutant	Potential Emissions (tpy)	Proposed Allowable Emissions (tpy)	
PM			PM - Particulate Matter PM ₁₀ - Particulate Matter less
PM_{10}			than 10 microns in size
PM _{2.5}			PM _{2.5} - Particulate Matter less than 2.5 microns in size
SO _x			SOx - Sulfur Oxides NOx - Nitrogen Oxides
NO _x			CO - Carbon Monoxide
СО			VOC - Volatile Organic Compound
VOC			Pb - Lead and lead compounds Fluorides - Gaseous and
Pb			particulates H ₂ SO ₄ - Sulfuric Acid Mist H ₂ S - Hydrogen Sulfide
Fluorides			TRS - Total Reduced Sulfur
H ₂ SO ₄			RSC - Reduced Sulfur Compounds
H_2S			_ '
TRS			1
RSC		100000	

Emissions calculations must include fugitive emissions if the source is one the following listed sources, pursuant to CAA Section 302(j):

- (a) Coal cleaning plants (with thermal dryers);
- (b) Kraft pulp mills;
- (c) Portland cement plants;
- (d) Primary zinc smelters;
- (e) Iron and steel mills:
- (f) Primary aluminum ore reduction plants;
- (g) Primary copper smelters;
- (h) Municipal incinerators capable of charging more than 250 tons of refuse per day;
- (i) Hydrofluoric, sulfuric, or nitric acid plants;
- (i) Petroleum refineries;
- (k) Lime plants;
- (1) Phosphate rock processing plants;
- (m) Coke oven batteries;
- (n) Sulfur recovery plants;
- (o) Carbon black plants (furnace process);
- (p) Primary lead smelters;
- (q) Fuel conversion plants;

- (r) Sintering plants;
- (s) Secondary metal production plants;
- (t) Chemical process plants
- (u) Fossil-fuel boilers (or combination thereof) totaling more than 250 million British thermal units per hour heat input:
- (v) Petroleum storage and transfer units with a total storage capacity exceeding 300,000 barrels;
- (w) Taconite ore processing plants;
- (x) Glass fiber processing plants;
- (y) Charcoal production plants;
- (z) Fossil fuel-fired steam electric plants of more that 250 million British thermal units per hour heat input, and
- (aa) Any other stationary source category which, as of August 7, 1980, is being regulated under section 111 or 112 of the Act.

E(ii) - Proposed New Construction at an Existing Source or Modification of an Existing Source

DSF EU 204 Emergency Generator

Pollutant	Current Actual Emissions (tpy)	Current Allowable Emissions (tpy)	Post-Change Potential Emissions (tpy)	Post-Change Allowable Emissions (tpy)	
PM	0.00	0.29	0.30	0.30	
PM_{10}	0.00	0.29	0.30	0.30	
PM _{2.5}	0.00	0.29	0.30	0.30	
SO_x	0.00	0.00	0.00	0.00	
NO _x	0.05	9.40	11.48	11.48	
CO	0.01	2.50	2.59	2.59	
VOC	0.00	0.18	0.27	0.27	
Pb	0.000	0.00	0.00	0.00	
Fluorides	0.000	0.00	0.00	0.00	
H ₂ SO ₄	0.000	0.00	0.00	0.00	
H_2S	0.000	0.00	0.00	0.00	
TRS	0.000	0.00	0.00	0.00	
RSC	0.00	0.00	0.00	0.00	

PM - Particulate Matter

 $PM_{10}\,$ - Particulate Matter less than 10 microns in size $PM_{2.5}\,$ - Particulate Matter less than 2.5 microns in size SOx - Sulfur Oxides

NOx - Nitrogen Oxides

CO - Carbon Monoxide

VOC - Volatile Organic Compound Pb -

Lead and lead compounds Fluorides -

Gaseous and particulates

H₂SO₄ - Sulfuric Acid Mist

H₂S - Hydrogen Sulfide

TRS - Total Reduced Sulfur

RSC - Reduced Sulfur Compounds

[Disclaimers] The public reporting and recordkeeping burden for this collection of information is estimated to average 20 hours per response, unless a modeling analysis is required. If a modeling analysis is required, the public reporting and recordkeeping burden for this collection of information is estimated to average 60 hours per response .Send comments on the Agency's need for this information, the accuracy of the provided burden estimates, and any suggested methods for minimizing respondent burden, including through the use of automated collection techniques to the Director, Collection Strategies Division, U.S. Environmental Protection Agency (2822T), 1200 Pennsylvania Ave., NW, Washington, D.C. 20460. Include the OMB control number in any correspondence. Do not send the completed form to this address.

FORM SYNMIN - New Source Review Synthetic Minor Limit Request Form, if synthetic minor limits are being requested.

Attached

Narrative description of the proposed production processes. This description should follow the flow of the process flow diagram to be submitted with this application.

EU 204 was installed in 1994 as an emergency generator. At the time of the application manufacturer emissions performance data for this generator were unavailable. SMSC used data from AP-42 Chapter 3 Section 4, Large Stationary Diesel and All Stationary Dual-Fuel Engines to estimate actual and potential emissions from EU 204 and to propose NOx emission limits for this emissions source. The Introduction to AP-42 discusses the uses of AP-42 data and states that:

Emission factors in AP-42 are neither EPA-recommended emission limits (e. g., best available control technology or BACT, or lowest achievable emission rate or LAER) nor standards (e. g., National Emission Standard for Hazardous Air Pollutants or NESHAP, or New Source Performance Standards or NSPS). Use of these factors as source-specific permit limits and/or as emission regulation compliance determinations is not recommended by EPA. Because emission factors essentially represent an average of a range of emission rates, approximately half of the subject sources will have emission rates greater than the emission factor and the other half will have emission rates less than the factor. As such, a permit limit using an AP-42 emission factor would result in half of the sources being in noncompliance.

Tests conducted on September 23, 2014 indicated that EU 204 exceeded the emission rates and limits established based on AP-42 emission factors. This permit amendment adjusts the NOx limits to reflect the tests results which are more accurate and more appropriate than AP-42 factors. The worst case test data indicated a 39.01 lb./hr. NOx emission rate at a 92% load. The proposed new lb./hr. NOx limit adjusts the tested emission rate up to 100% load.

			Proposed
		AP-42	New
	Test Data	/Spec	Limit
MMBtu/hr	11.23	11.75	12.17
NOx lb/hr	39.01	37.59	45.93
NOx			
lb/MMBtu	3.48	3.20	3.77
Fuel Use (gal)	82.00	85.72	88.90
Fuel Use gph	82.00	85.72	88.90
kW	1153	1250	1250
Нр	1548	1678	1678
% load	92%		100%

SMSC estimated the MMBtu/hr rating for EU 204 in the current permit based on AP-42 Chapter 03, Section 03 Table 3.3-1 footnote c:

Assumes 99% conversion of carbon in fuel to CO₂ with 87 weight % carbon in diesel, 86 weight % carbon in gasoline, average BSFC of 7,000 Btu/hp-hr, diesel heating value of 19,300 Btu/lb, and gasoline heating value of 20,300 Btu/lb.

MMBtu/hr = 1678 hp X 7000/1000000 = 11.75 MMBtu/hr

The test data indicated a higher MMBtu/hr rate (11.23 MMBTU/hr at 92% load) which adjusted to 100% load would be 12.17 MMBtu/hr.

SMSC estimated the existing fuel use limits using the same source:

GPH = 11.75 MMBtu/hr x 1000000/(19300 btu/lb ÷7.1 lbs/gallon) = 85.72 gph

Test data indicated EU 204 used 82 gallons per hour at 92% load. Adjusted to 100% load this becomes 88.90 gallons per hour. Based on the test data SMSC requests increasing the annual fuel limit from 42,859 gallons per year to 44,449 gallons per year.

The proposed changes increase lb/hr NOx limits from 37.59 lbs/hr to 45.93 lbs/hr, an 8.34 lb/hr increase. Based on test data, annual NOx emissions limits are increased from 9.40 tons per year to 11.48 tons per year (2.08 tons per year increase).

Proposed NOx Limits

	Thro	No	Ox		
Actual 9/1 Maximum 9/14			Limited	Max. Und Emissi	ontrolled ons [1]
(gal/hr)	(gal/yr)	(gal/yr)	(gal/yr)	lb/hr	tons/yr
88.90	778,751	186.0	44,449	45.93	11.48

Nitrogen Oxide (NOx) Limitations and Requirements:

1. EU 204

- a. Limit NO_X emissions to no greater than 45.93 pounds per hour expressed as NO_2 , averaged over the duration of the emission performance test.
- b. Limit NO_X emissions to no greater than 11.48 tons per year expressed as NO_2 , based on a 12 month rolling sum. Compliance with this limit shall be based on a rolling sum of monthly emissions during the previous 12 months.
- c. Limit fuel usage to ultra-low diesel fuel with a maximum sulfur content of 0.0015%.
- d. Limit fuel usage to 44,449 gallons per year, based on a 12 month rolling sum. Compliance with this limit shall be based on a rolling sum of monthly fuel usage (in gallons) during the previous 12 months.

Process flow chart identifying all proposed processing, combustion, handling, storage, and emission control equipment.

No change from current permit

A list and descriptions of all proposed emission units and air pollutiongenerating activities.

Source	EU	Location	Make	Model	Serial Number	Month/Yr Mfg.	Month/Yr Installed	Primary Fuel	Rated kW	Horse Power	MMBtu /hr
Diesel Generator	204	DSF	Energy Dynamics	8011250C	1DGN03437	Jul-94	Jul-94	Diesel	1250	1678	12.17

Type and quantity of fuels, including sulfur content of fuels, proposed to be used on a daily, annual and maximum hourly basis.

			Actual 9/13 -9/14
EU	(gal/hr)	Limited (gal/yr)	(gal/yr)
204	88.90	44,449	186.0

Type and quantity of raw materials used or final product produced proposed to be used on a daily, annual and maximum hourly basis. The relevant information is covered above, under fuels.

Proposed operating schedule, including number of hours per day, number of days per week and number of weeks per year.

The operating schedule is intermittent with the exception of the weekly maintenance schedule. Emergency operation is a random event. Load shed typically occurs during summer and winter peak periods and is intermittent, generally lasting a few hours and with 12 or more hours between events.

A list and description of all proposed emission controls, control efficiencies, emission limits, and monitoring for each emission unit and air pollution generating activity.

No change from existing permit.

Criteria Pollutant Emissions - Estimates of Current Actual Emissions, Current Allowable Emissions, Post- Change Uncontrolled Emissions, and Post-Change Allowable Emissions for the following air pollutants: particulate matter, PM_{10} , $PM_{2.5}$, sulfur oxides (SOx), nitrogen oxides (NOx), carbon monoxide (CO), volatile organic compound (VOC), lead (Pb) and lead compounds, fluorides (gaseous and particulate), sulfuric acid mist (H_2SO_4) , hydrogen sulfide (H_2S) , total reduced sulfur (TRS) and reduced sulfur compounds, including all calculations for the estimates.

Criteria Pollutant Emissions

			Current		Post Change	
			Actual Allowable		Uncontrolled	Allowable
Source	EU Nos.	Pollutant	Emissions	Emissions	Emissions	Emissions
DSF	204	PM	0.00	0.29	0.30	0.30
DSF	204	PM ₁₀	0.00	0.29	0.30	0.30
DSF	204	PM _{2.5}	0.00	0.29	0.30	0.30
DSF	204	SO ₂	0.00	0.00	0.00	0.00
DSF	204	со	0.05	9.40	11.48	11.48
DSF	204	NO _X	0.01	2.50	2.59	2.59
DSF	204	VOC	0.00	0.18	0.27	0.27
DSF	204	Pb	0.000	0.00	0.00	0.00
DSF	204	Fl	0.000	0.00	0.00	0.00
DSF	204	H ₂ SO ₄	0.000	0.00	0.00	0.00
DSF	204	H ₂ S	0.000	0.00	0.00	0.00
DSF	204	TRS	0.000	0.00	0.00	0.00

Modeling - Air Quality Impact

No change from existing permit

Analysis (AQIA) ESA (Endangered Species Act)

No change from existing permit

NHPA (National Historic Preservation Act)

No change from existing permit



United States Environmental Protection Agency Program

> Address Phone Fax Web address

Genevieve Damico, Chief, Air Permits Section U.S. Environmental Protection Agency, Region 5 77 West Jackson Blvd (AR-18J) Chicago, IL 60604

phone: (312) 353-4761 fax: (312) 385-5501 email: damico.genevieve@epa.gov

FEDERAL MINOR NEW SOURCE REVIEW PROGRAM IN INDIAN COUNTRY

Application For Synthetic Minor Limit

(Form SYNMIN)

Please submit information to:

Genevieve Damico, Chief, Air Permits Section U.S. Environmental Protection Agency, Region 5 77 West Jackson Blvd (AR-18J) Chicago, IL 60604

Phone: (312) 353-4761

A. GENERAL INFORMATION

Company Name Shakopee Mdewakanton Sioux Community		Source Name Dakotah! Sport and Fitness	
Company Contact or Owner Name Stanley Ellison	1	Title Director of Land and Natural Resources	
Mailing Address Shakopee Mdewakanton Sioux Co	mmunity , 2330 Sioux Tr	rail NW, Prior Lake, MN, 55372	
Email Address stan.ellison@shakopeedakota.org			
Telephone Number 952-496-6158	Facsimile Num	aber (952) 445-8906	
		1001 (754) 445-0700	

B. ATTACHMENTS

For each criteria air pollutant, hazardous air pollutant and for all emission units and air pollutantgenerating activities to be covered by a limitation, include the following:

- **Item 1** The proposed limitation and a description of its effect on current actual, allowable and the potential to emit.
- **Item 2** The proposed testing, monitoring, recordkeeping, and reporting requirements to be used to demonstrate and assure compliance with the proposed limitation.
- **Item 3** A description of estimated efficiency of air pollution control equipment under present or anticipated operating conditions, including documentation of the manufacturer specifications and guarantees.
- **Item 4** Estimates of the Post-Change Allowable Emissions that would result from compliance with the proposed limitation, including all calculations for the estimates.
 - Item 5 Estimates of the potential emissions of Greenhouse Gas (GHG) pollutants:

Attachments to Form SYNMIN

Item 1 - The proposed limitation and a description of its effect on current actual, allowable and the potential to emit.

EU 204 was installed in 1994 as an emergency generator. At the time of the application manufacturer emissions performance data for this generator were unavailable. SMSC used data from AP-42 Chapter 3 Section 4, Large Stationary Diesel and All Stationary Dual-Fuel Engines to estimate actual and potential emissions from EU 204 and to propose NOx emission limits for this emissions source. The Introduction to AP-42 discusses the uses of AP-42 data and states that:

Emission factors in AP-42 are neither EPA-recommended emission limits (e. g., best available control technology or BACT, or lowest achievable emission rate or LAER) nor standards (e. g., National Emission Standard for Hazardous Air Pollutants or NESHAP, or New Source Performance Standards or NSPS). Use of these factors as source-specific permit limits and/or as emission regulation compliance determinations is not recommended by EPA. Because emission factors essentially represent an average of a range of emission rates, approximately half of the subject sources will have emission rates greater than the emission factor and the other half will have emission rates less than the factor. As such, a permit limit using an AP-42 emission factor would result in half of the sources being in noncompliance.

Tests conducted on September 23, 2014 indicated that EU 204 exceeded the emission rates and limits established based on AP-42 emission factors. This permit amendment adjusts the NOx limits to reflect the tests results which are more accurate and more appropriate than AP-42 factors. The worst case test data indicated a 39.01 lb./hr. NOx emission rate at a 92% load. The proposed new lb./hr. NOx limit adjusts the tested emission rate up to 100% load.

		·	Proposed
		AP-42	New
	Test Data	/Spec	Limit
MMBtu/hr	11.23	11.75	12.17
NOx lb/hr	39.01	37.59	45.93
NOx			
lb/MMBtu	3.48	3.20	3.77
Fuel Use (gal)	82.00	85.72	88.90
Fuel Use gph	82.00	85.72	88.90
kW	1153	1250	1250
Нр	1548	1678	1678
% load	92%		100%

SMSC estimated the MMBtu/hr rating for EU 204 in the current permit based on AP-42 Chapter 03, Section 03 Table 3.3-1 footnote c:

Assumes 99% conversion of carbon in fuel to CO₂ with 87 weight % carbon in diesel, 86 weight % carbon in gasoline, average BSFC of 7,000 Btu/hp-hr, diesel heating value of 19,300 Btu/lb, and gasoline heating value of 20,300 Btu/lb.

MMBtu/hr = 1678 hp X 7000/1000000 = 11.75 MMBtu/hr

The test data indicated a higher MMBtu/hr rate (11.23 MMBTU/hr at 92% load) which adjusted to 100% load would be 12.17 MMBtu/hr.

SMSC estimated the existing fuel use limits using the same source:

 $GPH = 11.75 \text{ MMBtu/hr} \times 1000000/(19300 \text{ btu/lb} \div 7.1 \text{ lbs/gallon}) = 85.72 \text{ gph}$

Test data indicated EU 204 used 82 gallons per hour at 92% load. Adjusted to 100% load this becomes 88.90 gallons per hour. Based on the test data SMSC requests increasing the annual fuel limit from 42,859 gallons per year to 44,449 gallons per year.

The proposed changes increase lb/hr NOx limits from 37.59 lbs/hr to 45.93 lbs/hr, an 8.34 lb/hr increase. Based on test data, annual NOx emissions limits are increased from 9.40 tons per year to 11.48 tons per year (2.08 tons per year increase).

Proposed NOx Limits

	Thro	N	Ox		
	Maximum	Actual 9/13 Max. Unco m 9/14 Limited Emissio			
(gal/hr)	(gal/yr)	(gal/yr)	(gal/yr)	lb/hr	tons/yr
88.90	778,751	186.0	44,449	45.93	11.48

Nitrogen Oxide (NOx) Limitations and Requirements:

1. EU 204

- a. Limit NO_X emissions to no greater than 45.93 pounds per hour expressed as NO_2 , averaged over the duration of the emission performance test.
- b. Limit NO_X emissions to no greater than 11.48 tons per year expressed as NO_2 , based on a 12 month rolling sum. Compliance with this limit shall be based on a rolling sum of monthly emissions during the previous 12 months.
- c. Limit fuel usage to ultra low diesel fuel with a maximum sulfur content of 0.0015%.
- d. Limit fuel usage to 44,449 gallons per year, based on a 12 month rolling sum.
 Compliance with this limit shall be based on a rolling sum of monthly fuel usage (in gallons) during the previous 12 months.

Item 2 - The proposed testing, monitoring, recordkeeping, and reporting requirements to be used to demonstrate and assure compliance with the proposed limitation.

No change

Item 3 - A description of estimated efficiency of air pollution control equipment under present or anticipated operating conditions, including documentation of the manufacturer specifications and guarantees.

There is no control on EU 204. It is an emergency generator

Item 4 - Estimates of the Post-Change Allowable Emissions that would result from compliance with the proposed limitation, including all calculations for the estimates.

EU 204 is an emergency only generator and is permitted to operate 500 hours per year or less.

Proposed NOx Limits

Limited	Max. Controlled Emissions		
(gal/yr)	lb/hr	tons/yr	
44,449	45.93	11.48	

Item 5 – Estimates of the potential emissions of Greenhouse Gas (GHG) pollutants

	Current		Post Change	
	Actual Emissions	Allowable Emissions	Uncontrolled Emissions	Allowable Emissions
CO ₂	2.10	484.52	502.21	502.21
CH ₄	0.00	0.26	0.27	0.27
N ₂ O	0.00	0.00	0.00	0.00
Total CO₂e	2.13	491.27	509.21	509.21



Federal Operating Permit Program (40 CFR Part 71)

EMISSION CALCULATIONS (EMISS)

Calculate potential to emit (PTE) for applicability purposes and actual emissions for fee purposes for each emissions unit, control device, or alternative operating scenario identified in section I of form **GIS**. If form **FEE** does not need to be submitted with the application, do not calculate actual emissions.

A. Emissions Unit ID EU 204

B. Identification and Quantification of Emissions

First, list each air pollutant that is either regulated at the unit or present in major amounts, then list any other regulated pollutant (for fee calculation) not already listed. HAP may be simply listed as "HAP." Next, calculate PTE for applicability purposes and actual emissions for fee purposes for each pollutant. Do not calculate PTE for air pollutants listed solely for fee purposes. Include all fugitives for fee purposes. You may round to the nearest tenth of a ton for yearly values or tenth of a pound for hourly values.

	Emission Rates			
		Poter	ntial to Emit	
	Actual			
	Annual			
	Emissions	Hourly	Annual	
Air Pollutants	(tons/yr)	(lb/hr)	(tons/yr)	CAS No.
со	0.01	10.35	2.59	
NOx	0.05	45.93	11.48	
PM	0.00	1.22	0.30	
PM10	0.00	1.22	0.30	
PM2.5	0.00	1.22	0.30	
SO2	0.00	0.02	0.00	
VOC	0.00	1.10	0.27	
CO2e	2.13	2036.83	509.21	
Highest Single HAP (Benzene)	0.00	0.01	0.04	
All HAPs	0.00	0.02	0.08	



OMB No. 2060-0336. Approval Expires 04/30/2012

• .		,	(P)			
Federal Operating Permit Program (40 CFR Part	71)					
EMISSION UNIT DESCRIPTION FOR FUEL COMB	USTION SOURCE	ES (EUD-1)				
A. General Information						
Emissions unit ID <u>EU 204</u> Description	Emissions unit IDEU 204 DescriptionDSF Emergency only generator					
SIC Code (4-digit) <u>4911</u> SCC Code <u>203</u>	<u>300101</u>					
B. Emissions Unit Description						
Primary use <u>Emergency backup power</u> Tem	porary Source _	Yes <u>X</u> No				
Manufacturer Energy Dynamics Model No. 80:	<u>11250C</u>					
Serial Number <u>1DGN03437</u> Insta	allation Date <u>07</u>	/_01_/_94				
Boiler Type: Industrial boiler Proces	ss burner F	Electric utility boi	ler .			
Other (describe)						
Boiler horsepower rating	Boiler steam flo	ow (lb/hr)				
Type of Fuel-Burning Equipment (coal burning	only):					
Hand firedSpreader stokerUn	derfeed stoker	Overfe	ed stoker			
Traveling grateShaking gratePu	lverized, wet bed	d Pulverize	ed, dry bed			
Actual Heat InputMM BTU/hr M	ax. Design Heat	Input <u>12.17</u>	_MM BTU/hr			
C. Fuel Data						
Primary fuel type(s) <u>Diesel</u> Sta	Primary fuel type(s) Diesel Standby fuel type(s) none					
Describe each fuel you expected to use during	the term of the	permit.				
Fuel Type	Max. Sulfur Content (%)	Max. Ash Content (%)	BTU Value (cf, gal., or lb.)			
Diesel	0.0015	0	137,000 Btu/gal			

D. Fuel Usage Rates

Fuel Type	Annual Actual Usage	Maximum Usage	
		Hourly	Annual
Diesel	186 Gallons	88.9 gallons	44,449 gallons

		Houriy	Ailluai
Diesel	186 Gallons	88.9 gallons	44,449 gallons
E. Associated Air Pollution Control Equipmen	it		
Emissions unit ID <u>NA</u> Device type			_
Air pollutant(s) Controlled			
Model No Seria	l No		
Installation date/C	ontrol efficiency (%)		
Efficiency estimation method			
Ambient Impact Assessment			
This information must be completed by temporequirement for this emissions unit (this is not		ambient impact asses	ssment is an applicable
Stack height (ft) 9.92 Inside stac	k diameter (ft)	1.0	
Stack temp(°F)950.0 Design sta	ack flow rate (ACFM)	12,000.0	
Actual stack flow rate (ACFM)12,000.	O Velocity (ft/sec)	254.65	_